

Printer Control	Emulation Mode	IBM PPR
Font	Print Mode	LQ Courier
Font	Pitch	10 CPI
Font	Proportional Spacing	No
Font	Style	Normal
Font	Size	Single
Symbol Sets	Character Set	Set II
Symbol Sets	Language Set	Latin American
Symbol Sets	Zero Character	Slashed
Symbol Sets	Code Page	USA
rear Feed	Line Spacing	6 LPI
rear Feed	Form Tear-Off	Off
rear Feed	Skip Over Perforation	No
rear Feed	Page Width	13.6 "
rear Feed	Page Length	11 "
rear Feed	Gap Control	Auto Gap
bottom Feed	Line Spacing	6 LPI
bottom Feed	Form Tear-Off	Off
bottom Feed	Skip Over Perforation	No
bottom Feed	Page Width	13.6 "
bottom Feed	Page Length	11 "
bottom Feed	Gap Control	Auto Gap
top Feed	Line Spacing	6 LPI
top Feed	Bottom Margin	Valid
top Feed	Page Width	13.6 "
top Feed	Page Length	11 "
top Feed	Gap Control	Auto Gap
top Feed	Wait Time	1 sec
top Feed	Page Length Control	by MENU Setting
Set-Up	Graphics	Uni-directional
Set-Up	Receive Buffer Size	64K
Set-Up	Paper Out Override	No
Set-Up	Print Registration	0
Set-Up	Operator Panel Function	Full Operation
Set-Up	Reset Inhibit	No
Set-Up	Print Suppress Effective	Yes
Set-Up	Auto LF	No
Set-Up	Auto CR	No
Set-Up	SI Select Pitch (10CPI)	15 CPI
Set-Up	SI Select Pitch (12CPI)	12 CPI
Set-Up	Time Out Print	Valid
Set-Up	Auto Select	No
Set-Up	Ribbon Selection	Black Ribbon
Set-Up	Printhead Gap Adjust	0
Set-Up	Graphics Speed	Low
Parallel I/F	I-Prime	Buffer Print
Parallel I/F	Pin 18	+5v
Printer Control	Emulation Mode	IBM PPR